

SPECIFICATIONS

FG6-136 TD SWA

Make		FUSO
Range	Canter	
Model	FG6-136 TD SWA	
Model code	FG84PE6RBJ3	
Axle Layout	4X4	
Cab	Forward Control	
Crew	3 seating	
Vehicle type	Freight Carrier	
Mass Data (kg)		
GVM	Manufacturer's gross vehicle mass	5400
GCM	Manufacturer's gross combination mass	7000
D/T	Permissible max towing drawing vehicle mass	7000
GA-Front	Manufacturer's front axle mass	2600
GA-Rear	Manufacturer's rear axle mass	2800
V	Permissible maximum vehicle mass	5400
AF	Permissible maximum front axle mass	2600
AR	Permissible maximum rear axle mass	2800
UF	Unladen front axle mass	1785
UR	Unladen rear axle mass	765
UT (Tare)	Total unladen mass	2550
Permissible Body + Payload		2850
Fuel Tank (Litres)	Capacity	100
Dimensions (mm)		
OL	Overall length	6105
OW	Overall width	1995
CA	Cab to Axle	2880
OH	Overall height	2435
FOH	Front overhang	1130
ROH	Rear overhang	1475
WB	Wheelbase	3460
Performance		
Gradeability at Permissible Maximum Weight (V) (tan α)		60%
Maximum Speed (SA Legislation)		100 km/h
Minimum turning radius		6.8 m
Standard Equipment/features		
Antilock Braking System (ABS) Exhaust Brake System Lockable Fuel Tank Cap Manual window regulator Outside mirror with long stay Seatbelt for driver, front centre and driver assistant Ashtray on door for driver and assistant Cigarette lighter Sunvisor for Driver and assistant Interior mirror Heater and defroster Dual type electric horn All lamps with E.e mark Telescopic and tilt steering column with Steering lock Tachometer Standard tool set Limited Slip Differential (LSD) Low range and High range option (4WD) 2WD and 4WD option (option drive)		
Standard Services		
4 years / 240 000km warranty		
15 000km maintenance schedule		

Engine	
Make	FUSO
Model	4D34-2AT5
Configuration	4 inline
Capacity (cm3)	3908
Type	Four stroke water cooled direct injection diesel engine
Power at RPM	100 @ 2,900 - 2,900
Torque at RPM	370 @ 1,600 - 1,600
Emission standards	Euro II
Generator	24 Volt, 50 Amp
Air Cleaner	Cyclone filter paper type
Suction	Snorkel and rain cap
Governor	All speed mechanical governor
Transmission	
Make	FUSO
Model	M035S5
Type	Synchronmesh gears
Shift	Manual
No. of gears forward	5
Low gear ratio	0.722
High gear ratio	5.380
Clutch	
Make	FUSO
Model	C3W28D
Type	Hydraulic Single Dry Plate
Diameter (mm)	275
Drive Axle	
Make	FUSO
Model	D033HW/LS
Reduction type	Single reduction, Hypoid gear
Final Ratio	6.166
Suspension	
Front	Laminated leaf springs with shock absorbers
Rear	Laminated leaf springs with shock absorbers
Steering	
Telescopic and tilt steering column with steering lock	
Brakes	
System type	Hydraulic with vacuum servo assistance, dual circuit with ABS
Front	Drum
Rear	Drum
ABS	Yes
Park/Emergency System	Internal Expanding type on propeller shaft
Auxiliary Brakes	Exhaust brake
Tyres and Rims	
Tyre Sizes	10R17.5
Wheel type	Drum Type
Electrical	
System	24V

DIMENSIONS

